



Buima

Suspension grid

BUIMA®

BUIMA® – suspension grid

Contents


Cliq Grid 24 mm (15/16") and New Deco 24 mm (15/16")	01
Cliq Grid 15 mm (9/16")	02
Buimaline Grid (bolt-slot)	03
Drywall Grid	25

Buima Grid


acoustical ceiling suspension.

Cliq Grid 24 mm (15/16") , New Deco 24 mm (15/16")


These economical 24 mm systems interface perfectly with standard building components such as lighting and air diffusers.




BMC-24-3600




BCC-24-1200
BCC-24-600



BW51/24G-A-3600




BW50G-3000




BW50/15G-3000


	Tested according to ASTM C-635 / EN 13964 (Cliq grid)	Pcs/ Ctn	LM/ Ctn	KG/ Ctn	Ctns/ Pallet
BMND-24-3600	3600 mm Main Runner, (New Deco system), 24 mm (15/16"), white	25	91.5	~25	100
BCND-24-1200	1200 mm Cross Tee, 24 mm (15/16"), New Deco End, white	50	61	~12	84
BCND-24-600	600 mm Cross Tee, 24 mm (15/16"), New Deco End, white	75	45.75	~9	90
BW51/24G-A-3600	3600 mm Wall Angle, 24 mm x 24 mm (15/16"x15/16"), white	20	73.2	~12	144
BW50G-3000	3000 mm Wall Angle, 19 mm x 24 mm (3/4" x 15/16"), white	40	122	~20	90
BW50/15G-3000	3000 mm Shadow Mold, 24 mm x 15 mm x 8 mm x 15 mm, white	35	106.75	~25	to order



BMND-24-3125



BCND-24-1250
BCND-24-625




BW51/19A-3050

	Tested according to ASTM C-635 / EN 13964 (Cliq grid)	Pcs/ Ctn	LM/ Ctn	KG/ Ctn
BMND-24-3125	3125 mm Main Runner, (New Deco system), 24 mm (15/16"), white	25	78.125	~19
BCND-24-1250	1250 mm Cross Tee, 24 mm (15/16"), New Deco End, white	50	62.5	~13
BCND-24-625	625 mm Cross Tee, 24 mm (15/16"), New Deco End, white	75	46.875	~8
BW51/19A-3050	3050 mm Wall Angle, 22 mm x 19 mm, white	40	122	~17


Buima Grid

Cliq Grid 15 mm (9/16")


The narrow 9/16" face of this grid diminishes the effect of the grid module while still providing a landing plane for lighting and air dif- fusers. Cliq end cross tees provide override ends with staked-on clip connections. Hook end cross tees feature butt ends which are ideal for installing concealed systems or metal panels requiring a flat landing plane.



BMC-15-3000
BCC-15-1200
BCC-15-600



BW50G-3000




BW50/15G-3000

Tested according to ASTM C-635 / EN 13964 (Cliq grid)		Pcs/ Ctn	LM/ Ctn	KG/ Ctn	Ctns/ Pallet
BMC-15-3000	3000 mm Main Runner, (Cliq system), 15 mm (9/16"), white	20	61	~18	63
BCC-15-1200	1200 mm Cross Tee, 15 mm (9/16"), Cliq End, white	60	73.2	~21	63
BCC-15-600	600 mm Cross Tee, 15 mm (9/16"), Cliq End, white	60	36.6	~11	90
BW50G-3000	3000 mm Wall Angle, 19 mm x 24 mm (3/4" x 15/16"), white	40	122	~20	90
BW50/15G-3000	3000 mm Shadow Mold, 24 mm x 15 mm x 8 mm x 15 mm, white	35	106.75	~25	to order


Buima Grid

Buimaline Grid (bolt-slot)


Buimaline grid offers grid offers designers a more monolithic appearance as the grid and panel faces are in the same plane. The 1/4" slot is useful for partition attachment as well as signage placement. The recess can be white or black to accentuate the module lines. The corss tees have integral end details and mitered ends for tailored appearance.



BML-15-3000W
BCL-15-1200W
BCL-15-600W



BW50G-3000




BW50/15G-3000

Tested according to ASTM C-635 / EN 13964 (Cliq grid)		Pcs/ Ctn	LM/ Ctn	KG/ Ctn	Ctns/ Pallet
BML-15-3000W	3000 mm Main Runner, 14.3 mm (9/16"), Slotted, White / White recess	20	61	~19	42
BCL-15-1200W	1200 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / White recess, notched two sides	60	73.2	~19	42
BCL-15-1200W	1200 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / White recess, notched one side	60	73.2	~19	42
BCL-15-1200W	1200 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / White recess, no notches	60	73.2	~19	42
BCL-15-600W	600 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / White recess	60	36.6	~10	60
BW50G-3000	3000 mm Wall Angle, 19 mm x 24 mm (3/4" x 15/16"), white	40	122	~20	90
BW50/15G-3000	3000 mm Shadow Mold, 24 mm x 15 mm x 8 mm x 15 mm, white	35	106.75	~25	to order
BML-15-3000B	3000 mm Main Runner, 14.3 mm (9/16"), Slotted, White / Black recess	20	61	~19	42
BCL-15-1200B	1200 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / Black recess, notched two sides	60	73.2	~19	42
BCL-15-600B	600 mm Cross Tee, 14.3 mm (9/16"), Slotted, White / Black recess	60	36.6	~19	60


Grid submittal: BUIMA

Drywall Grid

These economical drywall systems interface perfectly with standard building components.



BMDW-38-3600
BCDW-38-1200
BCDW-38-600



BWDT-31-3600

Tested according to ASTM C-635 / EN 13964 (Cliq grid)		Pcs/ Ctn	LM/ Ctn	KG/ Ctn	Ctns/ Pallet
BMDW-38-3600	3600 mm Main Runner, 38 mm x 43 mm (1 1/2" x 1 11/16"), zinc	10	36.6	~19	70
BCDW-38-1200	1200 mm Cross tee, 38 mm x 43 mm (1 1/2" x 1 11/16"), zinc	32	39.04	~17	54
BCDW-38-600	600 mm Cross tee, 38 mm x 43 mm (1 1/2" x 1 11/16"), zinc	32	19.52	~9	81
BWDT-31-3600	3600 mm Wall angle, 31 mm x 31 mm (1 1/4" x 1 1/4"), zinc	20	73.2	~20	108



No responsibility is taken for the correctness of this information.

Buima

BUIMA GROUP INC.

Address: 13F., No. 880, Zhongzheng Road, Zhonghe District,
New Taipei City 235015, Taiwan, China